Release Notes V2.16

Optimisations

- The ECC 2 includes two clocks, the hardware- and the system clock. By using firmware version 2.16, the hardware clock is synchronised by system clock each 24 hours.

- While "summer time" is activated, the time stamp for the statistic file is based on system time instead of unix time.

- Taps belonging to hygiene group 8 participate to hygiene flushes again.

- If statistic data have been downloaded by USB stick once and deleted afterwards (function „write and clear"), further statistic data can be downloaded by USB stick again.

- Faulty statistic data are ignored during the statistic file creation process (*.csv). Therefore all data records are downloaded or rather deleted.

- During download process, the data base is checked and repaired if necessary. The function is indicated on the display.

- System based restarts of ECC-2, due to hudge statistic files, have been eliminated.

Performance of firmware update
0.1 Disable the storage of statistical data in the Web Browser of the ECC-2
0.2 Save the firmware (ECC2Update-Vx.xx.tar) to a USB memory stick.
0.3 Plug the USB memory stick into the ECC2 function controller.
Caution!
Only one ECC2Update file may be saved on the USB memory stick.
0.4 Follow the instructions on the display.

All parameter settings remain !

Upload of installation and operating instructions
0.5 Save the installation and operating instructions (18-15.291-xx.pdf) to a USB memory stick.
0.6 Plug the USB memory stick into the ECC2 function controller.
0.7 Select the menu item "Load Manuals".
0.8 Follow the instructions on the display.